

Parameter	Data source
CO ₂ Emissions From Bake Furnace Packing Materials (CWPB and SWPB)	
PCC: annual packing coke consumption (metric tons/metric ton baked anode)	0.015.
BA: annual baked anode production (metric tons)	Individual facility records.
S _{pc} : sulfur content in packing coke (percent weight)	2.
Ash _{pc} : ash content in packing coke (percent weight)	2.5.

[74 FR 56374, Oct. 30, 2009, as amended at 75 FR 79156, Dec. 17, 2010]

Subpart G—Ammonia Manufacturing

§ 98.70 Definition of source category.

The ammonia manufacturing source category comprises the process units listed in paragraphs (a) and (b) of this section.

(a) Ammonia manufacturing processes in which ammonia is manufactured from a fossil-based feedstock produced via steam reforming of a hydrocarbon.

(b) Ammonia manufacturing processes in which ammonia is manufactured through the gasification of solid and liquid raw material.

§ 98.71 Reporting threshold.

You must report GHG emissions under this subpart if your facility contains an ammonia manufacturing process and the facility meets the requirements of either § 98.2(a)(1) or (2).

§ 98.72 GHGs to report.

You must report:

(a) CO₂ process emissions from steam reforming of a hydrocarbon or the gasification of solid and liquid raw material, reported for each ammonia manufacturing process unit following the requirements of this subpart (CO₂ process emissions reported under this subpart may include CO₂ that is later consumed on site for urea production, and therefore is not released to the ambient air from the ammonia manufacturing process unit).

(b) CO₂, CH₄, and N₂O emissions from each stationary fuel combustion unit. You must report these emissions under

subpart C of this part (General Stationary Fuel Combustion Sources), by following the requirements of subpart C, except that for ammonia manufacturing processes subpart C does not apply to any CO₂ resulting from combustion of the waste recycle stream (commonly referred to as the purge gas stream).

(c) CO₂ emissions collected and transferred off site under subpart PP of this part (Suppliers of CO₂), following the requirements of subpart PP.

[74 FR 56374, Oct. 30, 2009, as amended at 75 FR 79156, Dec. 17, 2010]

§ 98.73 Calculating GHG emissions.

You must calculate and report the annual process CO₂ emissions from each ammonia manufacturing process unit using the procedures in either paragraph (a) or (b) of this section.

(a) Calculate and report under this subpart the process CO₂ emissions by operating and maintaining CEMS according to the Tier 4 Calculation Methodology specified in § 98.33(a)(4) and all associated requirements for Tier 4 in subpart C of this part (General Stationary Fuel Combustion Sources).

(b) Calculate and report under this subpart process CO₂ emissions using the procedures in paragraphs (b)(1) through (b)(5) of this section for gaseous feedstock, liquid feedstock, or solid feedstock, as applicable.

(1) *Gaseous feedstock.* You must calculate, from each ammonia manufacturing unit, the CO₂ process emissions from gaseous feedstock according to Equation G–1 of this section: